









RFP2020-01 Fixture Schedule

LIGHTING FIXTURE SCHEDULE										
IMAGE	TYPE	DESCRIPTION	LAMPS	VOLTAGE	MOUNTING	REMARKS	MANUFACTURER/MODEL	UNIT COUNT	Wattage	Total Watts
	A	WALL SURFACE MOUNTED LINEAR LED WITH ASSYMETTRIC OPTICS. EXTRUDED ALUMINUM HOUSING, POWDER COATED FINISH, TEMPERED GLASS LENS, OPERATING TEMPERATURVRE -20°, FIVE YEAR WARRANTY, IP 67 RATED	4100K, LED	277	CANTILEVERED FROM ROOFTOP (CONCRETE BEAMS)	REMOTE POWER SUPPLY, 17WATT/FT	INSIGHT LIGHTING MEDLEY MX-17-40K-ASY-U-D-EAS12-48-REM-NO-XX-RPS-96W OR EQUAL	26	68	1768
	A1	WALL SURFACE MOUNTED LINEAR LED WITH ASSYMETTRIC OPTICS. EXTRUDED ALUMINUM HOUSING, POWDER COATED FINISH, TEMPERED GLASS LENS, OPERATING TEMPERATURVRE -20°, FIVE YEAR WARRANTY, IP 67 RATED	4100K, LED	277	CANTILEVERED FROM ROOFTOP (CONCRETE BEAMS)	REMOTE POWER SUPPLY, 17WATT/FT	INSIGHT LIGHTING MEDLEY MX-6W-40K-ASY-D-EAS6-24-REM-NO-TN-LV OR EQUAL	11	34	374
	B	COLOR CHANGING AND ACTIVE WHITE ROTATABLE HEAVY DUTY DIE CAST ALUMINUM, POWDER COATED FINISH, TEMPERED GLASS LENS, OPERATING TEMPERATURVRE -25°, FIVE YEAR WARRANTY, WET LOCATION CERTIFIED	RGBW LED	277	SURFACE (SILL) MOUNTED UPLIGHT (CONCRETE)	NARROW BEAM SPREAD	INSIGHT LIGHTING MQ2-50W-RGBW-D/15-SM-277-DMXFX/XX	10	50	500
	C	COLOR CHANGING AND ACTIVE WHITE WINDOW REVEAL. DIE CAST ALUMINUM, POWDER COATED FINISH, EXTERIOR PARST STAINLESS STEEL, HIGH TRANSMISSION SAFETY GLASS, IP 65, 50,000 HOURS	RGBW LED	120	SURFACE (SILL) MOUNTED UPLIGHT (CONCRETE)	BATWING BEAM SPREAD DISTRIBUTION	ELECTRIX ILLUMINATION MARC-RGBW-12-X-6-B-MARC-U	33	12	396
	D	COLOR CHANGING AND ACTIVE WHITE INDIRECT 11" CYLINDER, EXTRUDED ALUMINUM, POWDER COATED FINISH, TEMPERED GLASS LENS, OPERATING TEMPERATURVRE -25°, FIVE YEAR WARRANTY, WET LOCATION CERTIFIED	RGBW LED	277	SURFACE (SILL) MOUNTED UPLIGHT (CONCRETE)	NARROW BEAM SPREAD	INSIGHT LIGHTING CYNE-15-RGBW-0-WMU-277-DMX-XX-CRF	22	15	330
	E	ARCHITECTURAL, LOW PROFILE, HIGH EFFICIENCY LED WALL PACK. ALUMINUM HOUSING, STAINLESS STEEL HARDWARE AND POWDER COATED, FIVE YEAR WARRANTY,	4000K, LED	277	WALL MOUNTED AT 10' ABOVE GROUND	18W	RAB SLIM 18N/PC	8	18	144
	E1	ARCHITECTURAL, LOW PROFILE, HIGH EFFICIENCY LED WALL PACK. ALUMINUM HOUSING, STAINLESS STEEL HARDWARE AND POWDER COATED, FIVE YEAR WARRANTY,	4000K, LED	277	WALL MOUNTED AT 10' ABOVE GROUND	24W	RAB BRISKM32L-740/PC	2	22	44
	F	CRESTRON DIGITAL COMMUNICATION LIGHTING CONTROL SYSTEM TO TIE INTO EXISTING BACNET SYSTEM	NA	277	SEE DWG. FOR LOCATIIONS	ONE PER GARAGE	CRESTRON GLDMX -1 UNIVERSE WITH CLASS 1 NEMA ENCLOSURE	3	0	0